Index

A

abbreviated choice item, 171, 173
abbreviated view, 687
abort function, 568, 572
accelerator keys, used in notices, 658
ACTION_MENU event, 279
ACTION_SELECT event, 126, 175
alarm system call, 462
applications, structure of, 41
Attr_attribute type, 582-583
Attr_avlist type, 583
ATTR_CONSUME macro, 587, 598
attr_create_avlist function, 583
attr_find function, 586
attribute, attribute-value pair, 22-23
  changing, 22
  consuming, 587
  customizable, 587
  FRAME_MAX_SIZE, 73
  FRAME_MIN_SIZE, 73
  FRAME_SHOW_RESIZE_CORNER, 73
  generic and common, described, 22
  HELP_STRING_FILENAME, 561
  naming conventions, 22
  PANEL_VALUE_STORED_LENGTH, 184
  SCROLLBAR_COMPUTE_SCROLL_PROC, 263
  SCROLLBAR_NORMALIZE_PROC, 263
  TTY_ARGV, 247
  WIN_MESSAGE_DATA, 131
  WIN_MESSAGE_FORMAT, 131
  WIN_MESSAGE_TYPE, 131
attribute-value lists, 582
ATTR_LIST attribute, 583
attr_next macro, 584
ATTR_PKG_UNUSED_FIRST macro, 594
ATTR_PKG_UNUSED_LAST macro, 594
ATTR_STANDARD_SIZE macro, 583
auto-expand, 98
auto-shrink, 98

B

base frame, closed, 66
  creating, 62
  defined, 61
basicLocale resources, 541
BitGravity, set for canvases, 88
  windows, 94
blocking, 479
busy frames, 74
BUT macro, 129
button item, 166
  label, 166
  selection, 167

C

callback procedure, 35, 116
callback style of programming, 35
canvas, about, 30, 85-86
  automatic sizing, 98
  callback procedures, 106
  controlling size of, 98
  creating, 88
  default input mask, 106
  drawing in, 89
  getting view windows, 104
  handling input, 105
  height of subwindow, 99
  model of, 86
  paint window, 86-87
  repaint procedure, 91-98
  repainting, 89, 94
  resize procedure, 100
  scrolling, 101
  splitting views, 102
  subclassed from openwin, 85
  subwindow, 85-86
  tracking changes in size, 100
  tracking events, 122

canvas (cont'd)
view window, 85-86
width of subwindow, 99
CANVAS package, 85-111
CANVAS_AUTO_CLEAR attribute, 93
CANVAS_AUTO_EXPAND attribute, 98
CANVAS_AUTO_SHRINK attribute, 98-99
CANVAS_CMS_REPAINT attribute, 94, 528
CANVAS_EACH_PAINT_WINDOW macro, 104
CANVAS_END_EACH macro, 104
CANVAS_FIXED_IMAGE attribute, 88, 94
canvas.h header file, 88
CANVAS_HEIGHT attribute, 99
CANVAS_MIN_PAINT_HEIGHT attribute, 99
CANVAS_MIN_PAINT_WIDTH attribute, 99
CANVAS_NTH_PAINT_WINDOW attribute, 104
CANVAS_PAINTWINDOW_ATTRS attribute, 461
CANVAS_REPAINT_PROC attribute, 91
CANVAS_RESIZE_PROC attribute, 100, 122
CANVAS_RETAINED attribute, 88
CANVAS_VIEWABLE_RECT attribute, 93
CANVAS_VIEW_PAINT_WINDOW attribute, 104-105
CANVAS_WIDTH attribute, 99
CANVAS_X_PAINT_WINDOW attribute, 94
cascading menu, (See pullright menu).
chained inheritance, 19
checkbox item, 171, 174
choice item, 171
abbreviated, 171, 173
checkbox, 171
checkboxes, 174
display, 171
exclusive and nonexclusive, 171-172
foreground color, 175
getting image, 173
layout, 171
notification, 175
parallel lists, 176
selection, 175
class, definition of, 580
generic, 580
subclass, 580
class hierarchy, 18
client, about, 5
events, 474, 509
messages, 116, 123, 130;
interpreting, 130;
sending and reading, 130
client data attribute, 199
clipboard, 220, 637
closing frames, (See iconification).
CMS package, 513-534, 516
CMS_BACKGROUND_PIXEL attribute, 521
CMS_COLOR_COUNT attribute, 516
CMS_COLOR_INDEX attribute, 523
CMS_COLORS attribute, 517
CMS_CONTROL_CMS attribute, 524
CMS_CONTROL_COLORS macro, 524
CMS_FOREGROUND_PIXEL attribute, 521
cms.h header file, 333
CMS_INDEX attribute, 516
CMS_INDEX_TABLE attribute, 519
CMS_NAME attribute, 519, 527
CMS_NAMED_COLORS attribute, 517
CMS_PIXEL attribute, 520
CMS_SIZE attribute, 516
CMS_TYPE attribute, 515
CMS_X_COLORS attribute, 518
collapsing expose events, 92
color, 513-534
background, 520
colormap segment, 513;
default, 515;
definition of, 519;
dynamic, 515;
static, 515
colormap table, definition of, 519
cursor, setting for, 333
definition of RGB, 519
foreground, 520
panel items, example of, 525
resources, 524
Xv_Screen, 516
color RGB, 517
color Xv_Screen, 516
colormap segment, types, 515
colormap segments, xv_find, 527
command frame, 27, 68
defined, 61
command-line option, -lc_basiclocale, 541
-lc_displaylang, 541
-lc_inputlang, 541
-lc_numeric, 541
-lc_timeformat, 541
common attributes, 22
compiling XView programs, 41
confirmation of quit, FRAME_NO_CONFIRM attribute, 67
connection, between server and client, 6
control area, implemented as panel, 153
create_cursor procedure, 333

curses(3X), 241, 247
cursor, about, 327
as font character, 330
color, 329
color, setting, 333
hotspot, 330
predefined, 330
Xv_Cursor, 327
CURSOR package, 327-335
CURSOR_BACKGROUND_COLOR, 333
CURSOR_DRAG_STATE attribute, 334
CURSOR_DRAG_TYPE attribute, 334
CURSOR_FOREGROUND_COLOR, 333
CURSOR_IMAGE attribute, 327
CURSOR_MASK_CHAR attribute, 330
cursors.h header file, 327
CURSOR_SRC_CHAR attribute, 330
CURSOR_STRING attribute, 334
CURSOR_XHOT attribute, 330
CURSOR_YHOT attribute, 330
customizable attributes, 587

D

DefaultColormap macro, 515
defaults, 381
package, 381-390
(see also resources)
defaults_get_boolean procedure, 385
defaults_get_character procedure, 387
defaults_get_enum procedure, 388
defaults_get_integer procedure, 387
defaults_get_string procedure, 387
defaults.h header file, 385
defaults_init procedure, 385
defaults_load_db procedure, 385
defaults_set_boolean procedure, 385
defaults_set_character procedure, 387
defaults_set_integer procedure, 387
defaults_set_string procedure, 387
defaults_store_db procedure, 385
delayed binding, 277, 339
DESTROY_CHECKING, 479, 494
DESTROY_CLEANUP, 494
destroying frames, 79
DESTROY_PROCESS_DEATH, 478, 494
DESTROY_SAVE_YOURSELF, 495
Destroy_status, 494
destruction of objects, 494
safe, 479
dgettext() procedure, 545
dispatching, explicit, 501
dispatching by Notifier, explicit, 498
implicit, 498
display, distinguished from screen, 6
Display structure, 350
displaying frames, 69
displayLang resources, 541
distributed processing, about, 7
DND_ACCEPT_CURSOR attribute, 441
DND_ACCEPT_X_CURSOR attribute, 441
DND_CURSOR attribute, 441
dnd_decode_drop() procedure, 442
dnd_done() procedure, 443
dnd_is_local() macro, 443
dnd_send_drop() procedure, 439
DND_TIMEOUT_VALUE attribute, 442
DND_TYPE attribute, 439
DND_X_CURSOR attribute, 441
dot files, 687
drag and drop, about, 433
accept cursor, 441
adding and deleting regions, 436
event handling, 437
receiving a drop, 442
registering drop-sites, 436
sending the drop, 439
sourcing the drag, 439
use with selection package, 441
DRAGDROP package, 433-456
dragdrop.h header file, 435
draw programs, 89
drawing in a canvas, 89
drop target item, 194
DROP_SITE_DEFAULT attribute, 436
DROP_SITE_DELETE_REGION attribute, 437
DROP_SITE_DELETE_REGION_PTR attribute, 437
DROP_SITE_EVENT_MASK attribute, 436, 438
DROP_SITE_ID attribute, 436, 438
DROP_SITE_ITEM package, 433-456
DROP_SITE_REGION attribute, 436
DROP_SITE_REGION_PTR attribute, 436
dup2 system call, 482

E

edit log, 222
editing, (see text subwindow)
enum, ITIMER_REAL, 467
ITIMER_VIRTUAL, 467
NOTIFY_ASYNC, 465
NOTIFY_SYNC, 465

enum (cont'd)
enumerated resources, 388
enumerated type, ERROR_NON_RECOVERABLE, 571
ERROR_RECOVERABLE, 571
environment variable, HELPPATH, 558, 562
error handling, advanced usage, 570
Xlib errors, 569
error recovery, 567-574
ERROR_BAD_ATTR attribute, 570
ERROR_BAD_VALUE attribute, 570
ERROR_CANNOT_GET attribute, 570
ERROR_CANNOT_SET attribute, 570
ERROR_CREATE_ONLY attribute, 570
ERROR_INVALID_OBJECT attribute, 571
ERROR_LAYER attribute, 571
ERROR_NON_RECOVERABLE enumerated type, 571
ERROR_PKG attribute, 571
error_proc procedure, 568
ERROR_RECOVERABLE enumerated type, 571
errors, advanced usage, 570
at run time, 567
recovery, 567
types, 570
Xlib, 569
ERROR_SERVER_ERROR attribute, 571
ERROR_SEVERITY attribute, 571
ERROR_STRING attribute, 571
escape sequences, sending to TTY subwindows, 243
event, ACTION_MENU, 279
ACTION_SELECT, 126, 175
Expose, 92
GraphicsExpose, 92
KBD_DONE, 121, 129
KBD_USE, 121, 129
LOC_DRAG, 120
LOC_MOVE, 106, 120
LOC_WINENTER, 106, 120, 129
LOC_WINEXIT, 106, 120
MapNotify, 54
MS_LEFT, 126
realize, 55
SCROLLBAR_REQUEST, 264
WIN_ASCII_EVENTS, 121
WIN_CIRCULATE_NOTIFY, 123
WIN_COLORMAP_NOTIFY, 120
WIN_CREATE_NOTIFY, 123
WIN_DESTROY_NOTIFY, 123
WIN_GRAPHICS_EXPOSE, 122
WIN_GRAVITY_NOTIFY, 123
WIN_MAP_NOTIFY, 123
WIN_META_EVENTS, 106
WIN_NO_EXPOSE, 122
WIN_REPAINT, 81, 92, 122
WIN_REPARENT_NOTIFY, 123
WIN_RESIZE, 81, 122-123
WIN_STRUCTURE_NOTIFY, 123
WIN_SUBSTRUCTURE_NOTIFY, 123
WIN_UNMAP_NOTIFY, 123
WIN_UP_ASCII_EVENTS, 121
WIN_UP_EVENTS, 106, 121
WM_SAVE_YOURSELF, 495
XClientMessage, 116
XClientMessageEvent, 131
event handling, in CANVAS package, 105
event_action macro, 126
event_button_is_down macro, 128
event-driven input handling, 460
event_id macro, 126
event_is_ascii macro, 127
event_is_button macro, 128
event_is_down macro, 126
event_is_iso macro, 127
event_is_key_bottom macro, 128
event_is_key_left macro, 128
event_is_key_right macro, 128
event_is_key_top macro, 128
event_is_up macro, 126
event_left_is_down macro, 128
event_middle_is_down macro, 128
event_right_is_down macro, 128
events, 9
about, 9, 116
classes of, 116
client, 509
communicating with client, 474
determining state of event, 126
differences between X and XView, 125
event ID, 117, 126
Event structure, 19, 124-126
event-to-action mapping, 117, 126; default for panel items, 206
keyboard, 121
masks, 116, 138
modifier keys, 126
mouse, 121
posting, 475
posting destroy, 478
registering, 118
relationship to Notifier, 35
repaint, 81, 122
resize, 81, 122
semantic, 117

events (cont'd)
XEvent structure, 125
event_string macro, 127
event_window macro, 125
event_xevent macro, 92
exclusive and nonexclusive choices, 171-172
exec system call, 482
exit function, 50, 570, 572
expanding size of canvas, 98
Expose event, 92

F

file chooser, about, 677
customization, 687
sorting, 686
file descriptors, use in Notifier, 479
File_chooser, object, 677
FILE_CHOOSER, package, 677
FILE_CHOOSER_ABBREV_VIEW attribute, 687
FILE_CHOOSER_APP_DIR attribute, 687
FILE_CHOOSER_AUTO_UPDATE attribute, 688
FILE_CHOOSER_CD_FUNC attribute, 683
FILE_CHOOSER_COMPARE_FUNC attribute, 684, 686
FILE_CHOOSER_CUSTOMIZE_OPEN attribute, 688
FILE_CHOOSER_DIRECTORY attribute, 683
FILE_CHOOSER_DOC_NAME attribute, 687
FILE_CHOOSER_EXTEN_FUNC attribute, 688
FILE_CHOOSER_EXTEN_HEIGHT attribute, 688
FILE_CHOOSER_FILTER_FUNC attribute, 683
FILE_CHOOSER_FILTER_MASK attribute, 684
FILE_CHOOSER_FILTER_STRING attribute, 684
FILE_CHOOSER_HISTORY_LIST attribute, 687
FILE_CHOOSER_MATCH_GLYPH attribute, 685
FILE_CHOOSER_MATCH_GLYPH_MASK attribute, 685
FILE_CHOOSER_NO_CONFIRM attribute, 683
FILE_CHOOSER_NOTIFY_FUNC attribute, 683
FILE_CHOOSER_OPEN macro, 677
FILE_CHOOSER_SAVE macro, 677
FILE_CHOOSER_SAVEAS macro, 677
FILE_CHOOSER_SAVE_TO_DIR attribute, 687
FILE_CHOOSER_SHOW_DOT_FILES, 687
FILE_CHOOSER_SHOW_DOT_FILES attribute, 687
FILE_CHOOSER_TYPE attribute, 677
FILE_LIST, 688, 690
files, reading, 480
filtering, 685
FIOASYNC, 462
FIONBIO, 462
flow of control in Notifier-based programs, 36
font, FONT_FAMILY_DEFAULT, 372
FONT_FAMILY_DEFAULT_FIXEDWIDTH, 372
FONT_STYLE_DEFAULT, 372
font conventions, xxxvi
font ID, 367
FONT package, 367-377
FONT_CHAR_HEIGHT attribute, 376
FONT_CHAR_WIDTH attribute, 376
FONT_DEFAULT_CHAR_HEIGHT attribute, 376
FONT_DEFAULT_CHAR_WIDTH attribute, 376
FONT_FAMILY attribute, 371
FONT_FAMILY_DEFAULT font, 372
FONT_FAMILY_DEFAULT_FIXEDWIDTH font, 372
FONT_INFO attribute, 375
FONT_NAME attribute, 375
FONT_RESCALE_OF attribute, 374
fonts, 25, 50, 367
creating, 368
dimensions, 375
family, 367, 371
rescaling, 374
scale, 367
scaling, 373
size, 367, 373
specifying font by name, 375
style, 367, 371
using xv_find, 368
WINDOW attributes, 373
FONT_SCALE attribute, 373
fonts.h header file, 368
FONT_SIZE attribute, 371, 373
FONT_SIZES_FOR_SCALE attribute, 373
FONT_STRING_DIMS attribute, 376
Font_string_dims structure, 376
FONT_STYLE attribute, 372
FONT_STYLE_DEFAULT font, 372
footer, FRAME_SHOW_FOOTER attribute, 65
of a frame, 63
fork system call, 482

frame, about, 26-28
- base frame, 26, 61-62
- closed base frame, 66
- command frame, 61, 68
- display, setting, 69
- headers and footers, 63
- in class hierarchy, 18
- initialization, 62
- modifying open/close using the Notifier, 491
- multiple screens, 351
- pop-up, 26
- providing visual feedback, 74
- role of window manager, 61
- size, setting, 74
- subframe, 61

FRAME package, 59-82, 69
FRAME_ACCELERATOR attribute, 147
FRAME_BUSY attribute, 74
FRAME_CLOSED attribute, 342
FRAME_CLOSED_RECT attribute, 66
FRAME_CMD package, 68-69
FRAME_CMD_DEFAULT_PIN_STATE attribute, 69
FRAME_CMD_PANEL attribute, 293
FRAME_CMD_PIN_STATE attribute, 69
FRAME_DONE_PROC attribute, 71
frame_fit_all macro, 77
FRAME_FOCUS_DIRECTION attribute, 147
FRAME_FOCUS_RIGHT, 147
FRAME_FOCUS_UP, 147
FRAME_FOCUS_WIN attribute, 146
frame_get_rect procedure, 74
FRAME_ICON attribute, 66
frame_kbd_use procedure, 146
FRAME_LABEL attribute, 64
FRAME_MAX_SIZE attribute, 73
FRAME_MENU_ADD attribute, 695
FRAME_MENU_COUNT attribute, 695
FRAME_MENU_DELETE attribute, 695
FRAME_MENUS, 695
FRAME_MENUS attribute, 695
FRAME_MIN_SIZE attribute, 73
FRAME_NO_CONFIRM attribute, 67
FRAME_NTH_SUBFRAME attribute, 76
FRAME_NTH_SUBWINDOW attribute, 76
frame_set_rect procedure, 74
FRAME_SHOW_FOOTER attribute, 65
FRAME_SHOW_HEADER attribute, 64
FRAME_SHOW_RESIZE_CORNER attribute, 73
FRAME_WM_COMMAND_ARGC attribute, 78
FRAME_WM_COMMAND_ARGC_ARGV attribute, 78, 495
FRAME_WM_COMMAND_ARGV attribute, 78
FRAME_WM_COMMAND_STRINGS attribute, 78
FRAME_X_ACCELERATOR attribute, 147
freeing the server, 359
FULLSCREEN package, 359

G

gap between panel items, 159
gauge item, 188
GC, about, 96-98
- font ID, 367
- fonts, 370
- repainting objects, example of, 98

generic, attributes, 22
- functions, table of, 21

generic object, 19, 24-25
getitimer system call, 462
gettext() procedure, 544
getting an object's package, 572
global variable, xv_default_server, 353
global variables, 199
glyphs, 178, 330, 367
grabbing the server, 359
graphics, 355
- CANVAS_X_PAINT_WINDOW, 94
- cursor images, 327
- draw programs, 89
- exposure events, 92, 122
- paint programs, 90
- rendering in color, 521
- rendering methods, 91
- rendering text, example of, 370
- SunView, 91
- text-based programs, 90
- visualization programs, 90
- Xlib drawing, example of, 333
- XView model, 91
- (see also server image)

GraphicsExpose event, 92

H

handle, for object, 19
header, FRAME_SHOW_HEADER attribute, 64
- of a frame, 63

header file, about, 42
- canvas.h, 88

header file (cont'd)
cms.h, 333
cursors.h, 327
defaults.h, 385
dragdrop.h, 435
fonts.h, 368
icon.h, 339
notice.h, 308, 655
notify.h, 463
openmenu.h, 277
panel.h, 155
rect.h, 66
screen.h, 350
sel_pkg.h, 397, 399
server.h, 353
signal.h, 465
svrimage.h, 356
textsw.h, 216
tty.h, 241
win_event.h, 119, 125
win_input.h, 119, 124-125
X.h, 119
Xlib.h, 96, 350
xv_error.h, 570
xview.h, 42
help, example, 559
installation, 562
help facilities, 557-564
help frame, 27
HELPPATH environment variable, 558, 562
HELP_STRING_FILENAME attribute, 561
hidden class, 85
hints, to window manager, 61
HISTORY_LIST, 687
HISTORY_MENU, 687

I

ICCCM, (See Inter-Client Communications Conventions Manual).
icon, 66
about, 34, 339
creating, 339
positioning image, 342
server image, 340
size, 344
text label, 344
ICON package, 339-345
icon.h header file, 339
iconification, 66, 340
ICON_IMAGE attribute, 342
ICON_IMAGE_RECT attribute, 342
ICON_LABEL attribute, 344
ICON_LABEL_RECT attribute, 344
ICON_MASK_IMAGE attribute, 344
ICON_TRANSPARENT attribute, 343
ICON_TRANSPARENT_LABEL attribute, 345
include files, (See header file).
inheritance, 19, 85, 88
initialization, 45, 62
(see also xv_init procedure)
input, about, 9
handling, event-driven, 460;
mainline, 459
handling of, 115-148
in CANVAS package, 105
input masks, 116
inputLang resources, 541
Inputmask structure, 119, 131-132
interclient communication, 9, 393-430, 635-652
interclient communications, 433-456
Inter-Client Communications Conventions Manual, 9
internationalization, 537-553
about, 537
attributes for gettext(), 549
bindtextdomain(), 546
creating text domain, 547
dgettext() procedure, 545
gettext() procedure, 544
handling text, 543
locale command-line options, 541
locale resources, 541
locale setting, 538
locale specification, 541
objects, 550
OPEN LOOK user interface, 539
POSIX categories, 542
textdomain(), 545
xview locale attributes, 540
interposition, 37, 488-498
scrolling, 264
intrinsics, definition of, 580
xview, 580
ioctl system call, 462
item, gauge, 188
ITIMER_REAL enum, 467
ITIMER_VIRTUAL enum, 467

K

KBD_DONE event, 121, 129
KBD_USE event, 121, 129
keyboard, event states, 126
keyboard events, 121
keyboard focus, about, 5
  defined by window manager, 9
  directing under program control, 129
  events, 121
  grabbing, 129, 359
keyboard focus item, notification, 192
  setting a value, 193
KEY_BOTTOM macro, 128
KEY_LEFT macro, 128
KEY_RIGHT macro, 128
KeySym, 117
KEY_TOP macro, 128

L

-lc_basiclocale command-line option, 541
-lc_displaylang command-line option, 541
-lc_inputlang command-line option, 541
-lc_numeric command-line option, 541
-lc_timeformat command-line option, 541
libraries, for XView, 42
line, editing in text subwindow, 226
list item, adding and deleting, 181
  displaying, 178
  notification, 183
  selection, 182
lists, attribute-value, 582
LOC_DRAG event, 120
LOC_MOVE event, 106, 120
LOC_WINENTER event, 106, 120, 129
LOC_WINEXIT event, 106, 120

M

macro, ATTR_CONSUME, 587, 598
  attr_next, 584
  ATTR_PKG_UNUSED_FIRST, 594
  ATTR_PKG_UNUSED_LAST, 594
  ATTR_STANDARD_SIZE, 583
  BUT, 129
  CANVAS_EACH_PAINT_WINDOW, 104
  CANVAS_END_EACH, 104
  CMS_CONTROL_COLORS, 524
  DefaultColormap, 515
  dnd_is_local(), 443
  event_action, 126
  event_button_is_down, 128
  event_id, 126
  event_is_ascii, 127
  event_is_button, 128
  event_is_down, 126
  event_is_iso, 127
  event_is_key_bottom, 128
  event_is_key_left, 128
  event_is_key_right, 128
  event_is_key_top, 128
  event_is_up, 126
  event_left_is_down, 128
  event_middle_is_down, 128
  event_right_is_down, 128
  event_string, 127
  event_window, 125
  event_xevent, 92
  frame_fit_all, 77
  KEY_BOTTOM, 128
  KEY_LEFT, 128
  KEY_RIGHT, 128
  KEY_TOP, 128
  OPENWIN_EACH_VIEW, 105
  PANEL_CHECK_BOX, 174
  PANEL_CHOICE_STACK, 173
  PANEL_EACH_ITEM, 165
  PANEL_END_EACH, 165
  panel_set_value, 193
  PANEL_TOGGLE, 172
  window_fit, 77, 164
  window_fit_height, 77, 164
  window_fit_width, 77, 164
  XDefaultColormap, 515
  xv_alloc, 596
  XV_ATTR, 583
  XV_DEFAULT_CMS_SIZE, 516
  XV_INIT_ARGS, 46
  XV_PRIVATE, 593
  XV_PUBLIC, 593
  XV_SERVER_FROM_WINDOW, 138
mainline input handling, 459
MapNotify event, 54
menu, about, 31, 273
  adding menu items, 285
  appending new item, 283
  creating, 277
  default item, 297
  destroying, 298
  displaying image, 284, 286
  finding items, 297
  freeing allocated strings, 299
  freeing pullright menus, 299

menu (cont'd)
generation procedures, 287
menu title, 282
notification procedures, 294
owner of, 277
pin-up, 292
position of menu item, 282
pullright, 285
pullright menus, 274
selected item, 297
setting inactive items, 294
string handling, 282
toggle (nonexclusive) settings, 291
XView implementation, 274
Menu accelerators, 695
menu buttons, on panels, 167
MENU package, 273-304, 277
MENU_ACCELERATOR attribute, 696
MENU_ACCELERATORS attribute, 696
MENU_ACTION_ACCELERATOR attribute, 696
MENU_ACTION_IMAGE attribute, 284
MENU_ACTION_ITEM attribute, 283-284
MENU_APPEND_ITEM attribute, 284
MENU_CHOICE_MENU package, 278
MENU_CLIENT_DATA attribute, 199, 300
MENU_COMMAND_MENU package, 277
MENU_DEFAULT_ITEM attribute, 297
MENU_DESCEND_FIRST attribute, 297
MENU_DONE_PROC attribute, 279, 293
MENU_FIRST_EVENT attribute, 279
MENU_GEN_PIN_WINDOW attribute, 292
MENU_GEN_PROC attribute, 287
menu_gen_proc procedure, 288
MENU_GEN_PULLRIGHT attribute, 287
MENU_GEN_PULLRIGHT_ITEM attribute, 288
MENU_IMAGE attribute, 284
MENU_IMAGES attribute, 286
MENU_INACTIVE attribute, 294
MENU_ITEM attribute, 283, 299
MENUITEM package, 283-284
MENU_LAST_EVENT attribute, 279
MENU_NCOLS attribute, 292
MENU_NITEMS attribute, 288
MENU_NOTIFY_PROC attribute, 282, 294
menu_notify_proc procedure, 282, 294
MENU_NOTIFY_STATUS attribute, 298
MENU_NROWS attribute, 292
MENU_NTH_ITEM attribute, 288
MENU_PARENT attribute, 290
MENU_PIN attribute, 293
MENU_PIN_PROC attribute, 293
MENU_PIN_WINDOW attribute, 293
MENU_PULLRIGHT attribute, 285
MENU_PULLRIGHT_IMAGE attribute, 285
MENU_PULLRIGHT_ITEM attribute, 285
MENU_RELEASE attribute, 285, 298
MENU_RELEASE_IMAGE attribute, 287
MENU_REMOVE attribute, 288
MENU_SELECTED_ITEM attribute, 297
menu_show procedure, 278-279
MENU_STRING attribute, 283-284
MENU_STRINGS attribute, 282
MENU_STRINGS_AND_ACCELERATORS attribute, 696
MENU_TITLE_ITEM attribute, 282
MENU_TOGGLE_MENU package, 278, 291
message item, 184
selection, 184
messages, client, 123
modifier keys, 126
modifying the display list, 686
monitoring scrolling events, 264
motion events, 120
mouse, button events, 121;
registering interest in, 119
button, re-mapping, 117
event states, 126
getting coordinate position, 330
motion events, 120
position, 124
mouseless model, 142
keyboard command mapping, 143
location cursor, 146
MS_LEFT event, 126
multiline text item, 188, 193

N

nonexclusive choice, 172
nonvisual objects, 349-363
about, 34
notice, about, 27, 307, 655
busy frames, 316
creating, 308, 655
destroying, 320
displaying, 308, 655
implementation, 655
origin, 657
responses, 311, 658
screen-locking, 316
standard, 313
status, 311
suppressing beep, 320, 661
triggers, 318, 659

notice (cont'd)
types, 313
NOTICE package, 307-324
use of FULLSCREEN package, 359
NOTICE_BLOCK_THREAD attribute, 313
NOTICE_BUSY_FRAMES attribute, 313, 316
NOTICE_BUTTON attribute, 658
NOTICE_BUTTON_NO attribute, 311
NOTICE_BUTTON_YES attribute, 311, 658
NOTICE_EVENT_PROC attribute, 315
NOTICE_FOCUS_XY attribute, 317, 657
notice.h header file, 308, 655
NOTICE_LOCK_SCREEN attribute, 313
NOTICE_MESSAGE_STRING attribute, 309
NOTICE_MESSAGE_STRINGS attribute, 309, 312, 658
NOTICE_MESSAGE_STRINGS_ARRAY_PTR attribute, 309, 574
NOTICE_NO attribute, 497
NOTICE_NO_BEEPING attribute, 661
notice_prompt procedure, 655
NOTICE_STATUS attribute, 311
NOTICE_TRIGGER attribute, 318
NOTICE_TRIGGER_EVENT attribute, 320
NOTICE_YES attribute, 497
notification, menus, 294
notification procedures, in a text subwindow, 233
Notifier, 459-510
about, 10, 459
base event handler, 488
client, 463
client events, 474
control, 498
definition, 461
destroy event delivery time, 479
error codes, 507-508
explicit dispatching, 498, 501
file descriptors, 479
flow of control in Notifier-based programs, 36
handling X events, 54
implicit dispatching, 498
interposing on frame open/close, 491
interposing on resize events, 493
interposition, 37, 488
miscellaneous issues, 509
operation, 461
overview, 35
pipes, 482
posting events, 475;
client, 476;
destroy, 478;
with an argument, 477
procedures of, 460
prohibited signals, 464
reading, 480
role of xv_main_loop procedure, 54
safe destruction, 479
signal handling, 464
SIGTERM handling, 470
timers, 467
Notifier procedures
notify_default_wait, 3, 472
notify_do_dispatch, 499
notify_interpose_destroy_func, 494
notify_interpose_event_func, 491
notify_next_event_func, 492
notify_post_destroy, 478
notify_post_event, 475
notify_post_event_and_arg, 477-478
notify_set_destroy_func, 464
notify_set_exception_func, 465
notify_set_input_func, 465, 480
notify_set_itimer_func, 462, 467
notify_set_output_func, 465, 480
notify_set_signal_func, 465-466
notify_set_wait3_func, 464, 471
notify_veto_destroy, 494
notify procedure, 35
Notify_arg, 475, 478
NOTIFY_ASYNC enum, 465
NOTIFY_BADF, 508
NOTIFY_BAD_ITIMER, 508
NOTIFY_BAD_SIGNAL, 508
Notify_client, 475
Notify_copy, 478
NOTIFY_COPY_NULL, 478
notify_default_wait3 procedure, 472
NOTIFY_DESTROY_VETOED, 479, 508
notify_dispatch procedure, 498
notify_do_dispatch procedure, 499
NOTIFY_DONE, 472, 475
notify_enable_rpc_svc(), function, 473
notify_errno, 507
Notify_error, 507
Notify_event, 475-476
Notify_event_type, 475
NOTIFY_FUNC_LIMIT, 508
notify.h header file, 463
NOTIFY_IGNORED, 472, 475-476, 490
NOTIFY_IMMEDIATE, 475-476
NOTIFY_INTERNAL_ERROR, 508
notify_interpose_destroy_func procedure, 463, 494
notify_interpose_event_func function, 206

notify_interpose_event_func procedure, 491
NOTIFY_INVAL, 479, 508
notify_next_event_func procedure, 492
NOTIFY_NO_CONDITION, 476, 508
NOTIFY_NOMEM, 508
NOTIFY_NOT_STARTED, 508
NOTIFY_OK, 508
notify_perror procedure, 508
notify_post_destroy procedure, 478
notify_post_event procedure, 475-476
notify_post_event_and_arg procedure, 477
notify_proc procedure, 233
Notify_release, 478
NOTIFY_RELEASE_NULL, 478
NOTIFY_SAFE, 475-476
notify_set_destroy_func procedure, 470
notify_set_event_func function, 598
notify_set_event_func procedure, 475
notify_set_exception_func procedure, 465
notify_set_input_func procedure, 465, 480
notify_set_itimer_func procedure, 462, 467
notify_set_output_func procedure, 465, 480
notify_set_signal_func procedure, 465-466
notify_set_wait3_func procedure, 246, 464, 471, 482
NOTIFY_SRCH, 508
notify_start procedure, 498
notify_stop procedure, 498
NOTIFY_SYNC enum, 465
NOTIFY_UNEXPECTED, 475
NOTIFY_UNKNOWN_CLIENT, 476, 508
NULL, 22
numeric keyboard focus item, 193
numeric resources, 541
numeric text item, 188

O

object-oriented programming, 17
objects, canvas subwindows, 30
  class hierarchy, 18
  destroying, 50, 493-494
  frames, 26
  Generic Object, 19, 24
  icons, 34
  menus, 31
  nonvisual, 18, 34
  panels, 30
  relationship to Notifier, 37
  scrollbars, 33
  text subwindows, 30
  use of object handle, 19
  windows, 25
opaque data types, 19
OPEN LOOK, about, 12
  as standard, 12
  control area, 153
  documentation, 13
  menus, 273
  scrollbars, 253
  text selection, 393
openmenu.h header file, 277
OPENWIN package, 85
  split views, 254
OPENWIN_AUTO_CLEAR attribute, 93
OpenWindows.KeyboardCommands, 143
OPENWIN_EACH_VIEW macro, 105
OPENWIN_NTH_VIEW attribute, 104
OPENWIN_SPLIT attribute, 103
OPENWIN_SPLIT_DESTROY_PROC attribute, 103
OPENWIN_SPLIT_INIT_PROC attribute, 103
override_redirect, 655
ownership of objects, 48

P

package, 18, 43
  CANVAS, 85-111
  CMS, 513-534, 516
  CURSOR, 327-335
  DRAGDROP, 433-456
  DROP_SITE_ITEM, 433-456
  FONT, 367-377
  FRAME, 59-82
  FRAME_CMD, 68
  FULLSCREEN, 359
  ICON, 339-345
  MENU, 273-304, 277
  MENU_CHOICE_MENU, 278
  MENU_COMMAND_MENU, 277
  MENUITEM, 283-284
  MENU_TOGGLE_MENU, 278, 291
  NOTICE, 307-324
  PANEL, 153-211, 155
  PANEL_ABBREV_MENU_BUTTON, 171
  PANEL_BUTTON, 166
  PANEL_CHOICE, 171
  PANEL_DROP_TARGET, 194
  PANEL_GAUGE, 188
  PANEL_LIST, 177
  PANEL_MESSAGE, 184
  PANEL_MULTILINE_TEXT_ITEM, 193
  PANEL_NUMERIC_TEXT, 193

package (cont'd)
PANEL_SCROLLABLE, 156
PANEL_SLIDER, 186
PANEL_TEXT, 188
PANEL_TOGGLE, 172
SCREEN, 350
SCROLLABLE_PANEL, 156
SCROLLBAR, 156, 253-270
SELECTION, 393
SELECTION_ITEM, 393
SELECTION_OWNER, 393
SELECTION_REQUESTOR, 393
SELN, 635-652
SERVER, 353
SERVER_IMAGE, 356
TEXTSW, 215-236
TTYSW, 241
Xv_pkg, 572
paint programs, 90
paint window, 87
controlling size, 99
definition of, 86
handling events, 106
panel, about, 30, 153
creating, 155
event handling, 155, 205
item (See panel item).
iterating over items, 165
layout, 159
minimum size, 164
panel item extensions, 620
scrollable, 156
sizing, 164
subclassed from window, 153
panel extensions, begin preview, 626
item handle procedures, 626
panel item, about, 153
attaching data, 199
button, 166
choice, 171
classes, 165
color, 525
creating, 157
destroying, 165
drop target, 194
drop target notify procedure, 198
extensions, 620
gap, 159
iteration, 165
layout, 160
menu buttons, 167
messages, 184
multiline text, 188
numeric text, 188
repainting, 205
scrolling lists, 177
setting values, 164
setting x and y coordinates, 162
slider, 186
text, 188
types, 157
values, 164
PANEL package, 153-211, 155
summary, 209
PANEL_ABBREV_MENU_BUTTON package, 171
PANEL_ACCEPT_KEYSTROKE attribute, 207
PANEL_BACKGROUND_PROC attribute, 206-207
PANEL_BORDER attribute, 160
PANEL_BUSY attribute, 167
PANEL_BUTTON package, 166
PANEL_CARET_ITEM attribute, 190, 206
PANEL_CHECK_BOX macro, 174
PANEL_CHOICE package, 171
PANEL_CHOICE_COLOR attribute, 175, 525
PANEL_CHOICE_IMAGE attribute, 173
PANEL_CHOICE_IMAGES attribute, 171
PANEL_CHOICE_NCOLS attribute, 171
PANEL_CHOICE_NROWS attribute, 171
PANEL_CHOICE_RECT attribute, 177
PANEL_CHOICE_STACK macro, 173
PANEL_CHOICE_STRING attribute, 171
PANEL_CHOICE_STRINGS attribute, 171, 583
PANEL_CHOICE_X attribute, 177
PANEL_CHOICE_XS attribute, 176
PANEL_CHOICE_Y attribute, 177
PANEL_CHOICE_YS attribute, 176
PANEL_CHOOSE_NONE attribute, 173
PANEL_CHOOSE_ONE attribute, 177, 182
PANEL_CLIENT_DATA attribute, 199-200
PANEL_DIRECTION attribute, 186
PANEL_DISPLAY_LEVEL attribute, 171
PANEL_DISPLAY_ROWS attribute, 193
PANEL_DROP_BUSY_GLYPH attribute, 196
PANEL_DROP_DND attribute, 197
PANEL_DROP_FULL attribute, 197
PANEL_DROP_GLYPH attribute, 196
PANEL_DROP_SEL_REQ attribute, 197
PANEL_DROP_TARGET package, 194
PANEL_EACH_ITEM macro, 165
PANEL_END_EACH macro, 165
PANEL_EVENT_PROC attribute, 206-207
PANEL_EXTRA_PAINT_HEIGHT attribute, 164

PANEL_EXTRA_PAINT_WIDTH attribute, 164
PANEL_FIRST_ITEM attribute, 165
PANEL_GAUGE package, 188
PANEL_GAUGE_WIDTH attribute, 188
panel.h header file, 155
PANEL_HORIZONTAL, value of PANEL_LAYOUT, 159
PANEL_INACTIVE attribute, 167
PANEL_ITEM_COLOR attribute, 521, 525
PANEL_ITEM_MENU, 184
PANEL_ITEM_X attribute, 162
PANEL_ITEM_X_GAP attribute, 159
PANEL_ITEM_Y attribute, 162
PANEL_ITEM_Y_GAP attribute, 159
PANEL_LABEL_BOLD attribute, 184
PANEL_LABEL_IMAGE attribute, 358
PANEL_LABEL_STRING attribute, 160, 166
PANEL_LABEL_WIDTH attribute, 170
PANEL_LAYOUT attribute, 159, 171, 176, 189
PANEL_LINE_BREAK_ACTION attribute, 194
PANEL_LIST package, 177
PANEL_LIST_CLIENT_DATA attribute, 184
PANEL_LIST_CLIENT_DATAS attribute, 184
PANEL_LIST_DELETE attribute, 181
PANEL_LIST_DELETE_INACTIVE_ROWS, 694
PANEL_LIST_DELETE_INACTIVE_ROWS attribute, 694
PANEL_LIST_DELETE_ROWS attribute, 181
PANEL_LIST_DELETE_SELECTED_ROWS attribute, 181
PANEL_LIST_DISPLAY_ROWS attribute, 178
PANEL_LIST_DO_DBL_CLICK attribute, 694
PANEL_LIST_EDIT, 184
PANEL_LIST_EXTENSION_DATA attribute, 695
PANEL_LIST_EXTENSION_DATAS attribute, 695
PANEL_LIST_FIRST_SELECTED attribute, 182
PANEL_LIST_FONT attribute, 178
PANEL_LIST_FONTS attribute, 178
PANEL_LIST_GLYPH attribute, 178
PANEL_LIST_GLYPHS attribute, 178
PANEL_LIST_INACTIVE attribute, 694
PANEL_LIST_INSERT attribute, 182
PANEL_LIST_INSERT_DUPLICATE attribute, 182
PANEL_LIST_INSERT_GLYPHS attribute, 181
PANEL_LIST_INSERT_STRINGS attribute, 181
PANEL_LIST_MASK_GLYPH attribute, 695
PANEL_LIST_MASK_GLYPHS attribute, 695
PANEL_LIST_MODE attribute, 184
PANEL_LIST_NEXT_SELECTED attribute, 182
PANEL_LIST_OP_DBL_CLICK, 694
PANEL_LIST_READ, 184
PANEL_LIST_ROW_HEIGHT attribute, 178
PANEL_LIST_ROW_VALUES, 691
PANEL_LIST_ROW_VALUES attribute, 691
PANEL_LIST_SELECT attribute, 182
PANEL_LIST_STRING attribute, 178
PANEL_LIST_STRINGS attribute, 178
PANEL_LIST_TITLE attribute, 178
PANEL_LIST_WIDTH attribute, 178
PANEL_MASK_CHAR attribute, 189
PANEL_MAX_TICK_STRING attribute, 186
PANEL_MAX_VALUE attribute, 186
PANEL_MAX_VALUE_STRING attribute, 186
PANEL_MESSAGE package, 184
PANEL_MIN_TICK_STRING attribute, 186
PANEL_MIN_VALUE attribute, 186
PANEL_MIN_VALUE_STRING attribute, 186
PANEL_MULTILINE_TEXT_ITEM package, 193
PANEL_NCHOICES attribute, 171
PANEL_NEXT_COL attribute, 159
PANEL_NEXT_ITEM attribute, 165
PANEL_NEXT_ROW attribute, 159
PANEL_NO_REDISPLAY_ITEM attribute, 625
PANEL_NOTIFY_LEVEL attribute, 187, 191
PANEL_NOTIFY_PROC attribute, 175
PANEL_NOTIFY_STATUS attribute, 167, 175
PANEL_NOTIFY_STRING attribute, 191
PANEL_NUMERIC_TEXT package, 193
PANEL_PAINT attribute, 205
panel_paint procedure, 205
PANEL_POST_EVENTS attribute, 497
PANEL_REPAINT_PROC attribute, 202
PANEL_SCROLLABLE package, 156
panel_set_value macro, 193
PANEL_SHOW_RANGE attribute, 186
PANEL_SHOW_VALUE attribute, 186
PANEL_SLIDER package, 186
PANEL_SLIDER_END_BOXES attribute, 186
PANEL_SLIDER_WIDTH attribute, 186
PANEL_TEXT package, 188
PANEL_TEXT_SELECT_LINE attribute, 191
PANEL_TICKS attribute, 186
PANEL_TOGGLE macro, 172
PANEL_VALUE attribute, 164-165
PANEL_VALUE_DISPLAY_LENGTH attribute, 189, 193
PANEL_VALUE_DISPLAY_WIDTH attribute, 189, 193

PANEL_VALUE_STORED_LENGTH attribute, 184, 189-190, 193
PANEL_VALUE_X attribute, 163
PANEL_VALUE_Y attribute, 163
PANEL_VERTICAL, value of PANEL_LAYOUT, 159
PANEL_WRAP_AT_CHAR, 194
PANEL_WRAP_AT_WORD, 194
parallel lists for choice item, 176
PATH_NAME, 690
pattern matching, (see text subwindow)
pclose system call, 462
pipe system call, 482
pipes, 482
pixel, definition of, 519
pixmap, 90
popen system call, 462
POSIX categories, 542
precedence of resource options, 53
primary selection, in a text subwindow, 232
property sheets, 153
pullright menus, 285
pushpin, about, 27, 69
  close procedure, 71
  command frame, 69
  use in menus, 292

Q

quit action, 67
quit confirmation, FRAME_NO_CONFIRM attribute, 67
quit.c program, 44

R

read system call, 479
readv system call, 509
realize event, 55
reaping child process, 471-472
Rect structure, 19, 66
rect.h header file, 66
Rectlist structure, 19, 95
remote procedure calling, RPC, 473
rendering graphics, 91
repaint
  canvas, about, 89;
    form of procedure, 91;
    procedures used to draw, 89-90;
    when procedure is called, 91
  event, 81, 122
  panel item, 205
reserved names, table of, 43
resize corners, displaying, 73
resize event, 81, 122
resize size, maximum and minimum, 73
resources, 381-390
  basicLocale, 541
  boolean, 385
  character, 387
  color, 524
  displayLang, 541
  enumerated, 388
  inputLang, 541
  integer, 386
  lookup, 388
  mouseless model, 145
  numeric, 541
  pairs, 388
  predefined default values, table of, 381
  string, 387
  timeFormat, 541
RGB, 517
rlimit system call, 509
RPC, interaction with, 473
run-time errors, 567

S

SCREEN package, 350
Screen structure, 350
Screen type, 350
screen.h header file, 350
SCREEN_NUMBER attribute, 350
screens, multiple, 351
SCREEN_SERVER attribute, 354
SCROLLABLE_PANEL package, 156
scrollbar, about, 33, 253
  creating, 254
  managing, 263
  OPEN LOOK description, 253
  relationship to objects, 256
  split views, 254
  use with canvases, 101
SCROLLBAR package, 156, 253-270
SCROLLBAR_COMPUTE_SCROLL_PROC attribute, 263
scrollbar_default_compute_scroll_proc procedure, 266
SCROLLBAR_NORMALIZE_PROC attribute, 263

SCROLLBAR_NOTIFY_CLIENT attribute, 264
SCROLLBAR_OBJECT_LENGTH attribute, 256
SCROLLBAR_PAGE_LENGTH attribute, 256, 259
SCROLLBAR_PIXELS_PER_UNIT attribute, 256, 258-259
SCROLLBAR_REQUEST event, 264
SCROLLBAR_SPLITTABLE attribute, 102
SCROLLBAR_VIEW_LENGTH attribute, 256, 259
SCROLLBAR_VIEW_START attribute, 256
scrolling, 266
  events, 264
  lists, 177
secondary selection, in a text subwindow, 232
SEL_APPEND_TYPE_NAMES attribute, 400
SEL_APPEND_TYPES attribute, 400
SEL_CONVERT_PROC attribute, 397, 403
sel_convert_proc() procedure, 404
SEL_COPY attribute, 413
SEL_DATA attribute, 401, 414
SEL_DONE_PROC attribute, 410
selection, about, 393, 635
  blocking request, 401
  conversion procedure, 403, 422
  copying to clipboard, 637
  getting from holder, 638
  in a text subwindow, 231
  incremental reply, 416
  non-blocking request, 402
  notify procedure, 421
  rank, 395, 637
  reply procedure attribute, 406
  reply procedure errors, 408
  selecting text, 393
  selection item object, 411
  sending data incrementally, 415
  service, 393, 635
  target type, 400
selection events, 130
selection model, 395
SELECTION package, 393
selection package, (See SELN package).
selection_ask procedure, 638-639, 646
selection_inquire procedure, 638
SELECTION_ITEM package, 393
SELECTION_OWNER package, 393
SELECTION_REQUESTOR package, 393
SEL_FIRST_ITEM attribute, 414
SEL_FORMAT attribute, 413
SEL_LENGTH attribute, 414
SEL_LOSE_PROC attribute, 410
SELN package, 635-652
SELN_CARET enum, 638
SEL_NEXT_ITEM attribute, 414
SELN_LEVEL_LINE attribute, 646
SELN_PRIMARY enum, 639
SELN_REQ_CONTENTS_ASCII attribute, 640, 645
SELN_REQ_FAKE_LEVEL attribute, 646
SELN_REQ_FIRST attribute, 641
SELN_REQ_FIRST_UNIT attribute, 646
SELN_REQ_LAST attribute, 641
SELN_REQ_LAST_UNIT attribute, 646
SELN_REQ_SET_LEVEL attribute, 646
Seln_request structure, 639, 641
SELN_SECONDARY enum, 639
SELN_SHELF enum, 639
SELN_UNKNOWN enum, 638
SELN_UNSPECIFIED enum, 639
SEL_OWN attribute, 397, 404
sel_pkg.h header file, 397, 399
sel_post_req() procedure, 402
SEL_PROP_DATA attribute, 418
SEL_PROP_FORMAT attribute, 418
SEL_PROP_INFO attribute, 418
SEL_PROP_LENGTH attribute, 418
SEL_PROP_TYPE attribute, 418
SEL_PROP_TYPE_NAME attribute, 418
SEL_RANK attribute, 398
SEL_RANK_NAME attribute, 398
SEL_REPLY_PROC attribute, 400, 406
SEL_TIME attribute, 399
SEL_TIMEOUT_VALUE attribute, 398
SEL_TYPE attribute, 400
SEL_TYPE_INDEX attribute, 418
SEL_TYPE_NAME attribute, 400
SEL_TYPE_NAMES attribute, 400
SEL_TYPES attribute, 400
sending client messages, 130
server, about, 5, 353
  freeing, 359
  grabbing, 359
  identifying, 354
  image (See server image)
  opening a connection, 353
  synchronizing, 354
  windows retained, 88
server image, 355
  as panel image, 358
  attached to other objects, 357
  creating, 356
  destroying pixmap, 357
  pixmaps, 355
  Server_image object, 356
  used for cursor, 327, 329

Server object, 353
SERVER package, 353
SERVER_ATOM attribute, 355
SERVER_ATOM_NAME attribute, 355
server-client model, 5
SERVER_EXTENSION_PROC attribute, 138
SERVER_EXTERNAL_XEVENT_MASK attribute, 139
SERVER_EXTERNAL_XEVENT_PROC attribute, 139
server.h header file, 353
SERVER_IMAGE package, 356
SERVER_IMAGE_BITMAP_FILE attribute, 357
SERVER_IMAGE_BITS attribute, 356
SERVER_IMAGE_CMS attribute, 357
SERVER_IMAGE_DEPTH attribute, 357
SERVER_IMAGE_PIXMAP attribute, 357
SERVER_IMAGE_SAVE_PIXMAP attribute, 357
SERVER_IMAGE_X_BITS attribute, 356
SERVER_NTH_SCREEN attribute, 351
SERVER_SYNC_AND_PROCESS_EVENTS attribute, 355
setjmp system call, 509
setpriority system call, 509
setquota system call, 509
settimer system call, 462
shelf, 637
sigaction (2), 462
SIGALRM, 464
sigblock system call, 509
SIGCHLD, 464, 471
SIGIO, 465
sigmask system call, 509
signal handling, 464
signal system call, 461, 486
  replacement for, 465
signal.h header file, 465
sigpause system call, 509
sigstack system call, 509
SIGTERM, 464, 470, 478
SIGURG, 465
sigvec (2), 462
sigvec system call, 509
SIGVTALRM system call, 464
sleep(), emulating, 502
slider item, 186
  selection, 187
soft function keys, 140
split views, about, 29
  function of scrollbar, 254
  in a text subwindow, 232
  in canvas, 102
static subclassing, 19
structure, Display, 350
  Event, 19, 124
  Font_string_dims, 376
  Inputmask, 119, 131-132
  Rect, 19, 66
  Rectlist, 19, 95
  Screen, 350
  Seln_request, 639, 641
  XEvent, 125
  XFontStruct, 375
  XTextExtents, 376
  Xv_Screen, 350
subclass, definition of, 580
subclassing, static, 580
subframe, 61, 68
subwindows, about, 29
  laying out in frames, 77
SunView, 11
  graphics, 91
svrimage.h header file, 356
system call, alarm, 462
  calls to avoid, 462
  dup2, 482
  exec, 482
  fork, 482
  getitimer, 462
  ioctl, 462
  pclose, 462
  pipe, 482
  popen, 462
  read, 479
  readv, 509
  rlimit, 509
  setjmp, 509
  setpriority, 509
  setquota, 509
  settimer, 462
  sigblock, 509
  sigmask, 509
  signal, 461, 486
  sigpause, 509
  sigstack, 509
  sigvec, 509
  SIGVTALRM, 464
  system, 462, 482
  umask, 509
  wait, 462
  wait3, 462, 471
  write, 479, 509
system system call, 462, 482

T

terminal emulator, (See TTY subwindow).
text item, 164, 188
  ASCII events, 206
  multiline, 193
  notification, 191
  numeric, 193
  selection, 190
text subwindow, about, 30, 215
  checking status, 218
  confirmation, 233
  contents of, 216
  creating, 216
  deleting text, 220
  destruction, 233
  determining what lines are visible, 227
  discarding edits, 224
  edit log, 222
  editing, 217
  emulating an editing character, 221
  getting a text selection, 231
  getting filename, 222
  index, 216
  interaction with file system, 223
  interposition, 236
  lines on screen and in file, 226
  loading a file, 217
  marking positions, 230
  notification, 233
  pattern matching, 228
  positioning text, 226
  positioning views, 226
  reading from, 219
  replacing characters, 221
  saving edits, 223
  scrolling, 227
  setting initial contents, 224
  setting insertion point, 219
  split views, 232
  storing edits, 223
  subclassed from OPENWIN, 216
  undo, 222
  use of clipboard, 220
  veto destroy, 233
  writing to, 219
text subwindow package, (see TEXTSW package)
text-based programs, 90
TEXTSW package, 215-236
Textsw_action attributes, 234
TEXTSW_ACTION_CAPS_LOCK attribute, 234
TEXTSW_ACTION_CHANGED_DIRECTORY attribute, 234
TEXTSW_ACTION_EDITED_FILE attribute, 234-235
TEXTSW_ACTION_EDITED_MEMORY attribute, 234
TEXTSW_ACTION_FILE_IS_READONLY attribute, 234
TEXTSW_ACTION_LOADED_FILE attribute, 234-235
TEXTSW_ACTION_TOOL_CLOSE attribute, 234
TEXTSW_ACTION_TOOL_DESTROY attribute, 234
TEXTSW_ACTION_TOOL_MGR attribute, 234
TEXTSW_ACTION_TOOL_QUIT attribute, 234
TEXTSW_ACTION_USING_MEMORY attribute, 234
textsw_add_mark procedure, 230
textsw_append_file_name procedure, 222
TEXTSW_CONTENTS attribute, 220, 225
textsw_delete procedure, 220
textsw_edit procedure, 221
textsw_erase procedure, 220-221
TEXTSW_FILE attribute, 217
TEXTSW_FILE_CONTENTS attribute, 224
textsw_file_lines_visible procedure, 227
textsw_find_bytes procedure, 228
textsw_find_mark procedure, 231
TEXTSW_FIRST attribute, 217
textsw_first procedure, 232
TEXTSW_FIRST_LINE attribute, 227
TEXTSW_FONT attribute, 216
TEXTSW_FOR_ALL_VIEWS attribute, 226
textsw.h header file, 216
TEXTSW_IGNORE_LIMIT attribute, 233
Textsw_index type, 216
textsw_index_for_file_line procedure, 227
TEXTSW_INFINITY value, 219-220
textsw_insert procedure, 219
TEXTSW_INSERT_FROM_FILE attribute, 225
TEXTSW_INSERTION_POINT attribute, 219
TEXTSW_INSERT_MAKES_VISIBLE attribute, 219, 228
TEXTSW_LENGTH attribute, 216
TEXTSW_LINE_BREAK_ACTION attribute, 226
textsw_match_bytes procedure, 229
TEXTSW_MEMORY_MAXIMUM attribute, 222
TEXTSW_MODIFIED attribute, 217
textsw_next procedure, 232
textsw_normalize_view procedure, 228

TEXTSW_NOTIFY_PROC attribute, 233
textsw_possibly_normalize procedure, 228
textsw_remove_mark procedure, 231
textsw_replace_bytes procedure, 222
textsw_reset procedure, 224
textsw_save procedure, 219, 223
textsw_screen_line_count procedure, 227
textsw_scroll_lines procedure, 227
textsw_set_selection procedure, 232
TEXTSW_STATUS attribute, 216, 218, 225
TEXTSW_STORE_CHANGES_FILE attribute, 223
textsw_store_file procedure, 219, 223
TEXTSW_WRAPAROUND_SIZE attribute, 222
tiled windows, definition of, 29
timeFormat resources, 541
timers, 467
toggle_notify procedure, 291
toolkit, (See X Window System, XView)
triggers, 318, 659
TTY subwindow, about, 241
  creating, 241
  escape sequences, 243
  input and output routines, 243
  monitoring, 246
  under program control, 242
TTY_ARGV attribute, 241, 246-247
tty.h header file, 241
TTY_PID attribute, 247
TTY_QUIT_ON_CHILD_DEATH attribute, 246
TTYSW package, 241
ttysw_input procedure, 242
ttysw_output procedure, 243
TTY_TTY_FD attribute, 247
type, about, 19
  Attr_attribute, 582-583
  Attr_avlist, 583
  defined in XView, 43
  Screen, 350
  Textsw_index, 216
  Window_rescale_state, 373
  XColor, 518
  XErrorEvent, 570
  Xv_Cursor, 327
  Xv_Font, 368
  Xv_object, 19, 49
  Xv_opaque, 19
  Xv_pkg, 572, 589
  Xv_singlecolor, 333
typecasting, 52

U

umask system call, 509
UNIX facilities used by applications, 462
UNIX system calls and XView, 462
user interface components, 7
user interface standards, 12

V

Version 3, 12
view window, 86
  definition of, 85
views, (See split views).
virtual keyboards, 140
  internationalization, 140
  language support, 140
visualization programs, 90

W

wait system call, 462
wait3 function, 246
wait3 system call, 462, 471-472
widget sets, 7
WIN_ASCII_EVENTS event, 121
WIN_BACKGROUND_COLOR attribute, 75, 521
WIN_BIT_GRAVITY attribute, 94
WIN_CIRCULATE_NOTIFY event, 123
WIN_CLIENT_DATA attribute, 199
WIN_CMS attribute, 513, 519, 524
WIN_CMS_NAME attribute, 519
WIN_COLLAPSE_EXPOSURES attribute, 92, 122
WIN_COLORMAP_NOTIFY event, 120
WIN_CONSUME_EVENT attribute, 106, 119
WIN_CONSUME_EVENTS attribute, 119
WIN_CONSUME_X_EVENT_MASK attribute, 118
WIN_CREATE_NOTIFY event, 123
WIN_DEPTH attribute, 25, 528
WIN_DESTROY_NOTIFY event, 123
window manager, authority of, 9
  definition, 9
  hints, 61
  role of, 61
window_fit macro, 77, 164
window_fit_height macro, 77, 164
window_fit_width macro, 77, 164
Window_rescale_state type, 373

windows, as objects, 25
creation, 55
win_event.h header file, 119, 125
WIN_EVENT_PROC attribute, 106, 124
WIN_EXTEND_TO_EDGE, 25
WIN_FOREGROUND_COLOR attribute, 75, 521
WIN_GRAB_ALL_INPUT attribute, 130
WIN_GRAPHICS_EXPOSE event, 122
WIN_GRAVITY_NOTIFY event, 123
WIN_IGNORE_EVENT attribute, 120
WIN_IGNORE_EVENTS attribute, 120
WIN_IGNORE_X_EVENT_MASK attribute, 118
win_input.h header file, 119, 124-125
WIN_INPUT_MASK attribute, 132
WIN_MAP_NOTIFY event, 123
WIN_MESSAGE_DATA attribute, 131
WIN_MESSAGE_FORMAT attribute, 131
WIN_MESSAGE_TYPE attribute, 131
WIN_META_EVENTS event, 106
WIN_MOUSE_XY attribute, 330
WIN_NO_CLIPPING attribute, 95
WIN_NO_EVENTS, 120
WIN_NO_EXPOSE event, 122
WIN_NOTIFY_IMMEDIATE_EVENT_PROC attribute, 598
WIN_NOTIFY_SAFE_EVENT_PROC attribute, 598
WIN_REPAINT event, 81, 92, 122
WIN_REPARENT_NOTIFY event, 123
WIN_RESIZE event, 81, 122-123
WIN_RETAINED attribute, 88, 101, 204
WIN_SCALE_EXTRALARGE, 373
WIN_SCALE_LARGE, 373
WIN_SCALE_MEDIUM, 373
WIN_SCALE_SMALL, 373
win_set_kbd_focus procedure, 129
WIN_SOFT_FNKEY_LABELS attribute, 141
WIN_STRUCTURE_NOTIFY event, 123
WIN_SUBSTRUCTURE_NOTIFY event, 123
WIN_TOP_LEVEL_NO_DECOR attribute, 78
WIN_UNMAP_NOTIFY event, 123
WIN_UP_ASCII_EVENTS event, 121
WIN_UP_EVENTS event, 106, 121
WIN_WINDOW_GRAVITY attribute, 94
WIN_X_COLOR_INDICES attribute, 520
WM_SAVE_YOURSELF event, 495
write system call, 479, 509

X

X Protocol, 6
X Window ID, (See XV_XID attribute).
X Window System, events, 92;
differences between X and XView, 125
extensibility, 8
interclient communications, 9, 393, 433, 635
overview, 3
protocol, 6
role of window manager, 9
server and client relationship, 5
software hierarchy, 7
specifying event masks, 118
toolkits, 7
X Window ID for paint window, 94
Xlib, 7
XAllocColor function, 518
XAllocColor procedure, 515
XAllocColorCells function, 518
XClientMessage event, 116
XClientMessageEvent event, 131
XColor type, 518
XCopyPlane procedure, 259
XDefaultColormap macro, 515
XErrorEvent type, 570
XEvent structure, 125
XFontStruct structure, 375
XGrabPointer procedure, 279
X.h header file, 119
Xlib, 7
repainting canvas, 95
using to draw, example, 333
Xlib.h header file, 96, 350
XLookupString procedure, 127
XNextEvent procedure, 131
XParseColor function, 517
XRebindKeysym procedure, 125, 127
XSendEvent procedure, 116, 130
XStoreColor function, 517
XStoreColors function, 518
XTextExtents structure, 376
xv_add_custom_attrs() procedure, 587
xv_alloc macro, 596
XV_APP_NAME attribute, 563
XV_ATTR macro, 583
XV_AUTO_CREATE attribute, 297, 612
xv_calloc function, 596
xv_check_bad_attr function, 586, 608
xv_col procedure, 163
xv_create procedure, 47
compared to xv_find(), 50
Xv_Cursor type, 327

XV_DECREMENT_REF_COUNT attribute, 169
XV_DEFAULT_CMS_SIZE macro, 516
xv_default_server global variable, 353
xv_destroy procedure, 50, 155
  used for frames, 79
xv_destroy_safe procedure, 50, 200, 479
XV_DISPLAY attribute, 350, 513
XV_DYNAMIC_CMS, 515
XV_END_CREATE attribute, 581, 600
XV_ERROR, 52
xv_error function, 567, 608
xv_error_format procedure, 568
xv_error.h header file, 570
XV_ERROR_PROC attribute, 568
xv_find, colormap segments, 527
  procedure, 49
Xv_Font type, 368
xv_get procedure, 51
XV_HEIGHT attribute, 355
XV_HELP_DATA attribute, 558
xv_help_show function, 561
XView, about, 3, 7, 9, 11-12
  as object-oriented system, 17
  compiling programs, 41
  concept of windows differs from X, 25
  data types, table of, 20
  example of programming interface, 43
  File Chooser, 677-702
  frames and subframes, 26
  generic functions, 21
  Generic Object, 19, 24
  internals, 579-632
  libraries, 42
  notification, 9, 35
  object class hierarchy, 18
  objects, 23-24;
    and owners, table of, 20;
    list of, 43
  overview, xxxiii
  packages, 18, 43
  programmer's model, 17-23
  programming interface, 41
  programs, initialization, 45, 62
  reserved names, 43
  reserved prefixes, 43
  structure of applications, 41
  subwindows, 29
  types, 43
  Version 3.2, 677-702
  window objects, 25
xview locale attributes, 540
xview.h header file, 42
XV_INCREMENT_REF_COUNT attribute, 169
xv_init procedure, 45, 62, 353
XV_INIT_ARGC_PTR_ARGV attribute, 46, 63
XV_INIT_ARGS attribute, 46, 63
XV_INIT_ARGS macro, 46
xv_input_readevent procedure, 119, 131, 361
XV_INSTANCE_NAME attribute, 390, 551
XV_KEY_DATA attribute, 199, 282
XV_KEY_DATA_REMOVE attribute, 202
XV_KEY_DATA_REMOVE_PROC attribute, 201
XV_LABEL attribute, 64, 344
XV_LC_BASIC_LOCALE attribute, 540
XV_LC_DISPLAY_LANG attribute, 540
XV_LC_INPUT_LANG attribute, 540
XV_LC_NUMERIC attribute, 540
XV_LC_TIME_FORMAT attribute, 540
XV_LOCALE_DIR attribute, 539, 547, 550
xv_main_loop procedure, 54, 498
XV_NAME attribute, 353
XV_OBJECT, 19
Xv_object type, 19, 49
Xv_opaque type, 19
Xv_pkg type, 572, 589
XV_PRIVATE macro, 593
XV_PUBLIC macro, 593
XV_RECT attribute, 582
XV_REF_COUNT attribute, 169
xv_row procedure, 163
Xv_Screen, 350, 516
XV_SCREEN attribute, 350, 354
xv_send_message procedure, 116, 130
XV_SERVER_FROM_WINDOW macro, 138
xv_set procedure, 51
XV_SHOW attribute, 69, 498
Xv_singlecolor attribute, 517
Xv_singlecolor type, 333
XV_STATIC_CMS, 515
XV_TYPE attribute, 572
XV_USAGE_PROC attribute, 46
XV_USE_DB attribute, 390, 551, 588
XV_USE_LOCALE attribute, 537-538
XV_VISUAL attribute, 528
XV_VISUAL_CLASS attribute, 528
XV_WIDTH attribute, 355
xv_window_loop procedure, 77
xv_window_return procedure, 77
XV_X attribute, 162
XV_X_ERROR_PROC attribute, 569
  to xv_init(), 569
XV_XID attribute, 94, 368
Xv_xrectlist, 97
XV_Y attribute, 162